




(182mm mono PERC half-cell, high-efficiency monocrystalline module)

400-415W 0-5W Positive Tolerance



MBB&SMBB Half-cut Cell Technology

New circuit design, lower internal current, and lower Rs loss.



High Power Density

A new generation of monocrystalline products with reduced resistive losses for greater power output.



Mechanical Properties

An aluminum frame in special design for better mechanical properties and more efficient installation.




Excellent Weather Resistance

The solar modules can meet the IEC standard requirements with strong resistant to risks such as salt spray, ammonia gas, dust, snail marks and electric potential induced attenuation.




4 Times 100% EL Detection

Guarantee no micro cracks



PRODUCT QUALITY SYSTEM & CERTIFICATION



■ JU New Linear Performance Warranty □ Standard Linear Performance Warranty

12years Material & process Warranty

25years Linear Performance Warranty

0.55% Linear Power Degradation

ELECTRICAL PROPERTIES

SM-182M-54H 108PCS

STC : irradiance, 1000W/m²; cell temperature, 25°C; spectral range, AM1.5

NOCT : irradiance, 800 W/m²; ambient temperature, 20 °C; spectral range, AM1.5; wind speed, 1m/s

	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum power - P _{mp} (W)	400	298	405	302	410	305	415	309
Open-circuit voltage - V _{oc} (V)	37.18	34.95	37.33	35.09	37.68	35.42	37.83	35.56
Short-circuit current - I _{sc} (A)	13.39	10.85	13.44	10.89	13.59	11.01	13.64	11.05
Maximum operating voltage - V _{mp} (V)	31.42	29.22	31.55	29.35	31.84	29.61	32.13	29.88
Maximum operating current - I _{mp} (A)	12.74	10.21	12.84	10.29	12.88	10.31	12.92	10.34
Module conversion efficiency - η _m	20.48%		20.74%		20.99%		21.25%	
Power tolerance (W)	(0, +5)							
Mechanical load	Front5400Pa/Back2400Pa							
Maximum system voltage (V)	1500							
Maximum series fuse rating (A)	25							
Operating temperature	-40~+85°C							

STRUCTURAL CHARACTERISTICS

Module dimensions(L*W*H)	1722 x 1134 x 30mm
Weight	21kg
Cell quantity	108PCS
Cell model	PERC Monocrystalline182 x 91mm
Glass	3.2mm AR, High Transmission, tempered glass
Frame	Anodized aluminium alloy
Junction box	IP68 Rated
Output line	4.0mm ² , wire length 300mm
Connector	MC4 Compatible




TEMPERATURE CHARACTERISTIC

Temperature coefficient (P _{max})	-0.35% / °C
Temperature coefficient (V _{oc})	-0.27% / °C
Temperature coefficient (I _{sc})	+0.05% / °C
NMOT	45±2°C

PACKAGING

Container	40HQ
PCS / Pallet	36
PCS / Container	936

PRODUCT ASSEMBLY DRAWING(mm)



20GW OEM/ODM Solar Customization
WWW.SOLAR-FOREST.COM +86 0538 5076188



Taishan ChuangGu Industrial Park,
 No. 3168 Taishan Street, Taian