

Efficiency

- Advanced MPPT with up to 99.9% efficiency
- Multiple charge and discharge modes are available

Safety

- 360 degrees of security from hardware tosoftware
- Multiple safety approvals available

All in one

- Support for many types of batteries
- Supports Li-ion battery BMS communication

Reliable

- Outputs high-quality pure sine wave AC power
- Reliable output for long periods at rated power

User-Friendly

- Industrial design with a modern aesthetic look
- Easy to install and simple to use

Intelligent

- Exclusive Li-ion battery BMS dual activation
- Support for remote monitoring of operating

Application scenario













Telecom

MODEL	HSI 5500P	CAN SE
INVERTER		
Rated Output Power	5,500W	
Max.Peak Power	11,000VA	
Rated Output Voltage	230Vac (single phase/three phase-paralleled)	1
Load Capacity of Motors	4HP	
Rated AC Frequency	50Hz/60Hz	1
Waveform	Pure Sine Wave	
Switch Time	10ms (typical)	
Parallel Capacity	1–6	
BATTERY		
Battery Type	Lead-acid / Li-ion / User defined	1
Rated Battery Voltage	48V	
Voltage Range	40~60Vdc	1
Max.MPPT Charging Current	100A	1
Max.Mains/Generator Charging Current	60A	1
Max.Hybrid Charging Current	100A	1
PV INPUT		
Num. of MPPT Trackers	1	
Max.PV Array Power	6,000W	
Max.Input Current	22A	
Max.Voltage of Open Circuit	50 <mark>0Vdc</mark>	
MPPT Voltage Range	120-450Vdc	
UTILITY/ GENERATOR INPUT		
Input Voltage Range	UPS mode: 170~280Vac; APL mode: 90~280Vac	1
Frequency Range	50/60Hz	
Bypass Overload Current	40A	
EFFICIENCY		
MPPT Tracking Efficiency	99.9%	
Max. Battery Inverter Efficiency	92%	
GENERAL		
Dimensions	426*322*124mm (1.40*1.06*0.41ft)	
Weight	10.5kg (23.15lb)	
Protection Degree	IP20, Indor Only	
Operating Temperature Range	–10°C~55°C	
Noise	≤60dB	
Cooling Method	Internal Fan	
Warranty	1.5 Years	
COMMUNICATION		
Embedded Interfaces	RS485 / USB / Dry contact	1
External Modules (Optional)	Wi-Fi / GPRS	1
CERTIFICATION		
Safety	CE(IEC 62109-1)/ CETL(UL 1741 C22.2 NO.107.1) /FCC/SAA	
EMC	EN61000	